

CLAIMS

1. (Canceled)
2. (Canceled)
3. (Canceled)
4. (Canceled)
4. (Canceled)
5. (Canceled)

7. (Previously presented) A cochlear implant system for a patient's cochlea comprising:
at least one electrode for electrical coupling with the patient's cochlea;
an internal coil for implanting in the patient to drive the electrode;
a microphone for outputting electrical sound signals in response to external sounds;
an oscillator for generating an electrical analog carrier signal having a frequency greater than 20 kHz;
a modulator for modulating the carrier signal with the sound signals to generate a modulated signal; and
an external coil for magnetically coupling the modulated signal to the internal coil such that the modulated signal is electrically applied to the cochlea.

8. (Original) The system of claim 7, wherein the modulator is an amplitude modulator.

9. (Original) The system of claim 7, wherein the modulator is a frequency modulator.

10. (Original) The system of claim 7, wherein the electrical analog carrier signal has a frequency of at least 32 kHz.

AMENDMENT

PAGE 2 OF 5

DOCKET NO. 1420-2
APPLICATION NO. 09/478,136

11. (Original) The system of claim 10, wherein the modulator is an amplitude modulator.
12. (Original) The system of claim 10, wherein the modulator is a frequency modulator.

AMENDMENT

PAGE 3 OF 5

DOCKET NO. 1420-2
APPLICATION NO. 09/478,136